INSTALLATION OF AIR / WATER SYRINGE REPAIR KIT

Air/Water Syringe Repair Kit (General) Product #: A113-019 / Retail Price: \$10.00

Air/ Water Syringe Repair Kit (Euro) Product #: A113-403 / Retail Price: \$15.95

110duct π. A113-403 / Retail 111cc. \$13.73

(Tools needed: Small Allen Key or a Hex Key)

Note: Petroleum Based Lubricant is needed for this repair

REMOVAL & INSTALLATION (GENERA – SQUARE HEADED SYRINGE)

- 1. **DEPRESSURIZE** dental station.
- 2. **REMOVE** PIN from the side of the SRINGE HOUSING by using a small PAPER CLIP or small ALLEN WRENCH.
- 3. **REMOVE BOTH** BUTTONS by PULLING straight OUT.
- 4. **REMOVE BOTH** VALVE CORES by UNSCREWING with tool that comes with the kit.
- 5. **CLEAN BOTH** BUTTON HOLES with alcohol and a Q-Tip to remove deposits.
- 6. Using a **PETROLEUM BASED LUBRICANT**, now you need to lubricate the O Rings. This must be done **BEFORE** you **INSTALL** the VALVE CORES.
- 7. **INSTALL NEW** VALVE CORES, using the VALVE CORE TOOL that comes with the kit.
- 8. **INSTALL NEW BUTTONS. REPLACE PIN on the side of the HOUSING.**

REMOVAL & INSTALLATION (EURO – ROUND HEADED SYRINGE)

- 1. **DEPRESSURIZE** dental station.
- 2. **REMOVE** PIN from the side of the SYRINGE HOUSING.
- 3. **REMOVE BOTH BUTTONS and SPRINGS.**
- 4. **CLEAN BOTH** BUTTON HOLES with alcohol and a Q-Tip to remove deposits.
- 5. LUBRICATE the O-RINGS.
- 6. **INSTALL NEW SPRINGS**, smaller side UP.
- 7. INSTALL NEW BUTTONS by PUSHING into ASSEMBLY all the way.
- 8. **REPLACE** PIN on the side of the HOUSING.