

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)
 VAC EVACUATION SYSTEM CLEANER

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name HYSAN CORP. & PROPERPAC, INC.	Emergency Telephone Number 312/523-1010 708-395-0070
Address (Number, Street, City, State, and ZIP Code) 4309 S.MORGAN ST. CHICAGO, IL. 60609	Telephone Number for Information 312/376-8981
	Date Prepared 6/5/87
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
SODIUM SILICATE C.A.S. NO.6834-92-0	N.E.	N.E.	2mg/m ³ (as NaOH)	1-5
2-BUTOXYETHANOL C.A.S. NO. 111-76-2	50ppm -skin-	25ppm -skin-	N.E.	1-5

Section III — Physical/Chemical Characteristics

Boiling Point	214°F	Specific Gravity (H ₂ O = 1)	1.08
Vapor Pressure (mm Hg.)	18	Melting Point	32°F
Vapor Density (AIR = 1)	<1	Evaporation Rate (Butyl Acetate = 1)	<1
Solubility in Water	COMPLETE		
Appearance and Odor	Clear thin liquid having a mild odor.		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) NONE T.C.C.	Flammable Limits NONE	LEL	UEL
Extinguishing Media WATER			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
VAC EVACUATION SYSTEM CLEANER

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name
HYSAN CORP. & PROPERPAC, INC.
Address (Number, Street, City, State, and ZIP Code)
4309 S.MORGAN ST.

CHICAGO, IL. 60609

Emergency Telephone Number
312/523-1010 708-395-0070
Telephone Number for Information
312/376-8981
Date Prepared
6/5/87
Signature of Preparer (optional)

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
SODIUM SILICATE C.A.S. NO.6834-92-0	N.E.	N.E.	2mg/m ³ (as NaOH)	1-5
2-BUTOXYETHANOL C.A.S. NO. 111-76-2	50ppm -skin-	25ppm -skin-	N.E.	1-5

Section III -- Physical/Chemical Characteristics

Boiling Point	214° F	Specific Gravity (H₂O = 1)	1.08
Vapor Pressure (mm Hg.)	18	Melting Point	32° F
Vapor Density (AIR = 1)	<1	Evaporation Rate (Butyl Acetate = 1)	<1
Solubility in Water	COMPLETE		
Appearance and Odor	Clear thin liquid having a mild odor.		

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used)	NONE T.C.C.	Flammable Limits	NONE	LEL	UEL
Extinguishing Media	WATER				
Special Fire Fighting Procedures	NONE				
Unusual Fire and Explosion Hazards	NONE				